

**REMARKS**

These remarks follow the order of the paragraphs of the office action. Relevant portions of the office communication are shown indented and italicized.

*Claim 1 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.*

*Claim 1 is now 2 sentences long, a period falling at end of line 1 on page 3 of the amendment. A claim can only be 1 sentence long*

In response, the applicant respectfully states that claim 1 is amended to be one sentence. This overcomes the rejection of claim 1 under 35 U.S.C. 112, second paragraph. Claim 1 is definite and particularly points out and distinctly claim the subject matter which applicant regards as the invention.

*The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:*

*(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains.*

*Patentability shall not be negated by the manner in which the invention was made.*

*Claim 1 is rejected under 35 U.S.C. 103(a) as being unpatentable over Willars et al in view of Carlsson and Engelhart and Miernik et al.*

In response, the applicant respectfully states that Claims 1 as being unpatentable by the invention of Willars and Carlsson and Engelhart and Miernik. The present invention, claimed in Claims 1, provides access to wireless communication

"wherein a network control unit identifies availability of different communication networks for a communication device. The communication device is notified of a recommendation of identified communication networks. In response to this notification,

1           the communication device initiates access to the recommended communication network  
2           for establishing a communication channel."

3   Thus the invention in claim 1 is directed to methods for managing network resources for  
4   wireless communication, automatically executed by an network control unit. The network  
5   control unit being external to the communication device. It enables a communication device to  
6   "vertically handover" a communication channel, so that devices can switch communications  
7   from one type of network to another or can establish communication on a recommended network.

8   Whereas, the cited art to Willars, US Patent 7,072,656, filed: February 8, 2002, is entitled:  
9   "Handover in a shared radio access network environment using subscriber-dependent neighbor  
10   cell lists". The Willars abstract reads:

11           "In a radio access network (14) comprising a serving radio network control node  
12           (26.sub.1) and a drift radio network control node (26.sub.2), a determination is first made  
13           that a target cell controlled by the drift radio network control node should be prepared for  
14           handover with respect to a user equipment unit (30). The target cell is neighbored by a set  
15           of neighboring cells, the set of neighboring cells including a first subset of neighboring  
16           cells and a second subset of neighboring cells, a handover involving the user equipment  
17           unit being permitted for a cell of the first subset but not for a cell of the second subset. In  
18           accordance with the determination, a message including a filtered list of cells is sent to  
19           the user equipment unit, the filtered list of cells including the first subset but not the  
20           second subset. The filtered list of cells can comprise, for example, a list of cells for whose  
21           frequencies the user equipment unit is to perform measurements. Which nodes perform  
22           the actions of (1) determining an allowed area(s) for the user equipment unit; and (2)  
23           preparing the filtered list of cells using the allowed area(s) depends on which of various  
24           alternative implementations are utilized ".

25   Thus, Willars is directed to handover in a shared radio access network environment using  
26   subscriber-dependent neighbor cell lists. Willars is apparently not concerned with an external  
27   network control unit managing network resources for wireless communication, automatically  
28   executed by the network control unit. Willars is concerned with handover neighbor cell lists.  
29   Willars is not concerned with network resource management or provision of network specific

1 requirements. Willars is not concerned with enabling a communication device to “vertically  
2 handover” a communication channel, so that devices can switch communications from one type  
3 of network to another or can establish communication on a recommended network

4 The further cited art to Carlsson, US Patent 2003/0119524, filed: December 22, 2001, is entitled:  
5 “Locating packet-switched mobile terminals using network initiated artificial cell hops”. The  
6 Carlsson abstract reads:

7 “Determining the position of a mobile terminal operating in a packet-switched  
8 communications system based on timing advance values obtained through network  
9 initiated artificial cell hops. The mobile terminal may be instructed to perform a series of  
10 artificial cell changes so that timing advance values may be obtained for the mobile  
11 terminal with respect to a plurality of base stations. The position of the mobile terminal is  
12 then determined based on the timing advance values, optionally supplemented by signal  
13 strength measurements. The mobile terminal may contact a network entity via the base  
14 station in each cell before being instructed to change to the next base station. Or, the  
15 mobile terminal may be supplied with a list of base stations to contact, with the mobile  
16 terminal transmitting short access bursts to the base station in a given cell before  
17 automatically tuning to the next cell, without waiting for an acknowledgment. ”.

18 Thus Carlsson is directed to position determination of a mobile terminal operating in a  
19 packet-switched communications system based on timing advance values obtained through  
20 network initiated artificial cell hops. Carlsson is also not concerned with an external network  
21 control unit managing network resources for wireless communication, automatically executed by  
22 the network control unit, and doesn't support Willars in this deficiency.

23 The still further cited art to Engelhart, US Patent 2004/0203580, filed: September 25, 2002, is  
24 entitled: “Virtual subscriber network”. The Engelhart abstract reads:

25 “A user device (e.g., a mobile telephone) communicates with an access node in a manner  
26 that causes the access node to provide call control and service options available through  
27 the access node. The capability and cost information is presented to a user device

1 subscriber. The user device communicates to the access node a selection of call control  
2 and service options to use with the device”.

3 Thus, Engelhart is directed to a virtual subscriber network in which a user device communicates  
4 with an access node in a manner that causes the access node to provide call control and service  
5 options available through the access node. Engelhart is also not concerned with an external  
6 network control unit managing network resources for wireless communication, automatically  
7 executed by the network control unit, and doesn't support Willars in this deficiency.

8 The still further cited art to Miernik, US Patent 7177641, filed: January 11, 2002, is entitled:  
9 “System and method for identifying a wireless serving node for a mobile unit”. The Miernik  
10 abstract reads:

11 “A system and method for identifying a wireless serving node for a mobile unit include  
12 the ability to receive a wireless registration request at a control node for a wireless  
13 serving node cluster and determine a control node associated with the registration request  
14 by using an algorithm on a mobile unit identifier in the registration request. The system  
15 and method also include the ability to generate a wireless registration response containing  
16 an identifier for the control node associated with the registration request if the control  
17 node is not the control node associated with the registration request”.

18 Thus, Miernik is directed to identifying a wireless serving node for a mobile unit include the  
19 ability to receive a wireless registration request at a control node for a wireless serving node  
20 cluster and determine a control node associated with the registration request by using an  
21 algorithm on a mobile unit identifier in the registration request. Miernik is also not concerned  
22 with an external network control unit managing network resources for wireless communication,  
23 automatically executed by the network control unit, and doesn't support Willars in this  
24 deficiency.

25 Thus, the combination fails to teach the elements of claim 1, or make claim 1 obvious, and claim  
26 1 is allowable over the combined art.

1 Furthermore, there is apparently no reason to make the four way combination except in  
2 apparently using hindsight and attempting to find a combination that has all the elements of claim  
3 1. Use of hindsight is not permitted. One skilled in the art would not have an inkling of making  
4 the combination of the four disparate references. Apparently the reference fail to refer to one  
5 another, as required in a 103 obviousness rejection. Besides even the combination fails to teach  
6 all the elements of claim 1, or make claim 1 obvious.

7 Claim 1 reads:

8 1. A method for managing network resources for wireless communication, comprising  
9 steps being automatically executed by a network control unit, said steps comprising:

10 identifying availability of different communication networks for a communication device,

11 notifying the communication device of a recommendation of identified communication  
12 networks which recommendation is binding for the communication device to connect to  
13 such recommended network,

14 determining a at least rough location of the communication device, and

15 identifying communication networks covering the device's location;

16 identifying communication networks covering the device's location according to a  
17 look-up table;

18 identifying access capability of the communication device to other communication  
19 networks;

20 identifying communication networks covering the device's location and being accessible  
21 for the communication device; and wherein:

1 communication networks are recommended according to communication costs;

2 communication networks are recommended according to a current load;

3 communication networks are recommended according to bandwidth properties;

4 communication networks are recommended according to a customer profile;

5 a hand over process for establishing a communication channel on a recommended

6 communication network is started after the communication device is notified;

7 the identification of available networks is triggered by a network control unit;

8 the identification of available networks is triggered periodically;

9 the identification of available networks is triggered when a physical movement of the  
10 communication device is detected; and

11 the identification of available networks is triggered by a capacity shortage on at least one  
12 of the networks.

13 These steps are not taught or alluded to by Willars with or without Carlsson, Engelhart and  
14 Miernik.

15 The office communication continues:

16 *Willars et al disclose in col. 5, lines 17 et seq., a technique to provide a mobile phone a*  
17 *list of neighboring cells that are adapted to that specific mobile's subscription.*

18 Willars et al disclose in col. 5, lines 17-52 reads:

1 "What is needed, therefore, and an object of the present invention, is a technique to  
2 provide the mobile a list of neighbor cells adapted to that specific mobile's subscription.

3  
4 BRIEF SUMMARY

5  
6 In a radio access network comprising a serving radio network control node and a drift  
7 radio network control node, a determination is first made that a target cell controlled by  
8 the drift radio network control node should be prepared for handover with respect to a  
9 user equipment unit. The target cell is neighbored by a set of neighboring cells, the set of  
10 neighboring cells including a first subset of neighboring cells and a second subset of  
11 neighboring cells, with the user equipment unit being permitted access to radio resources  
12 or to handover to cells in the first subset but not cells in the second subset. In accordance  
13 with the determination, a message including a filtered list of cells is sent to the user  
14 equipment unit, the filtered list of cells including the first subset but not the second  
15 subset. The filtered list of cells can comprise, for example, a list of cells for whose  
16 frequencies the user equipment unit is to perform measurements. Which nodes perform  
17 the actions of (1) determining an allowed area(s) for the user equipment unit; and (2)  
18 preparing the filtered list of cells using the allowed area(s) depends on which of various  
19 alternative implementations are utilized.

20 In accordance with a first alternative, the drift radio network control node both  
21 determines the allowed area(s) for the user equipment unit and performs the filtering. In  
22 particular, the serving radio network control node transmits to the drift radio network  
23 control node an identification of the target cell and an identification of the user equipment  
24 unit. The drift radio network control node determines the allowed area(s) and performs  
25 the filtering, after which the drift radio network control node transmits to the serving  
26 radio network control node the filtered list."

27 This apparently includes all of Willars cited against claim 1. A review shows indeed that it fails  
28 to allude to the elements of claim 1. It provides Willars' embodiment for "a technique to provide  
29 the mobile a list of neighbor cells adapted to that specific mobile's subscription." Claim 1 is not

1 concerned with neighbor cells, a list of neighbor cells, or any thing adapted to that specific  
2 mobile's subscription. This has little if any, relevance to "managing network resources for  
3 wireless communication, comprising steps being automatically executed by a network control  
4 unit, as in claim 1. Willars is directed to neighbor cells and has no other interest of managing  
5 network resources.

6 Claim 1 is directed managing network resources, concerned with determining a network has the  
7 required resources in terms of processing capability, or network bandwidth, or similar, to  
8 establish such link. It is not concerned with 'neighboring cells' for 'handover', as id Willars.

9 Page 4 of the present specification upon which claim 1 is based, reads:

10 In order to give the communication device advice which network to access, the network  
11 control unit is identifying availability of different communication networks for the  
12 communication device as a particular network has to be at least available in a sense of  
13 generally providing services in the device's location. This may preferably refer to the fact  
14 that coverage is physically provided by a particular network at the user's location, and / or  
15 preferably refer to the fact that the particular network may establish a communications  
16 link to the user, i.e. the network has the required resources in terms of processing  
17 capability, or network bandwidth, or similar, to establish such link. The results of the  
18 identification process are transmitted to the communication device. But not necessarily all  
19 results are subject to a message to the communication device. The network control unit  
20 might take a selection from the identified available networks and may notify the  
21 communication device only on one or more selected ones - these are recommended ones -  
22 out of the identified available networks. There might be different criteria applied to derive  
23 the recommended networks from the identified networks. There might be a number n of  
24 recommended networks with  $0 \leq n \leq m$ , and m being the amount of identified  
25 available networks. A recommendation of a network can basically be interpreted as  
26 binding for the communication device to connect to, or can be interpreted as suggestion  
27 to do so.

1 The office communication continues:

2 *In line 23 of col. 5 Willars et al disclose that a determination is first made that a target*  
3 *cell controlled by the drift node's controller should be prepared for a handover. The*  
4 *target cell is neighbored by other cells, with the mobile station being permitted to access*  
5 *radio resources or to handover to cells in one subset of cells but not permitted to handoff*  
6 *to other cells. A filtered list of cells is sent to the user equipment (UE) which only*  
7 *includes the cells which the radio network's controller will allow the UE to access. In*  
8 *lines 43 et seq., Willars et al disclose that the radio network's control node determines*  
9 *the allowed areas for the UE and also filters out the non-allowed cell areas, presumably*  
10 *those cell areas that would not support the UE's subscription requests. In col. 4, lines 28*  
11 *et seq.,*

12 In response, the applicants respectfully states that indeed Willars'

13 The present specification end of page 4 over to page 5 reads:

14 Basically, the invention enables a communication device to "vertically handover" a  
15 communication channel, that is to say that devices can switch communications from one  
16 type of network to another or can establish communication on a recommended network,  
17 for example in order to increase communications bandwidth, to lower cost, or to optimize  
18 bandwidth utilization from the network operator's point of view. Basically, the network  
19 control unit is controlling this process, at least initiating. A network operator is provided  
20 with adequate means - that is basically the network control unit - to assign  
21 communication devices to the "right" network when more than one is available.

22 As now the communication device is guided by the network to perform a vertical  
23 hand-over, a need for active scanning by the device is eliminated, thereby saving  
24 communication bandwidth and reducing power consumption of the communication  
25 device. Furthermore, globalized optimization of network resources over all devices  
26 present within the diverse networks administered and operated through one single  
27 operator become possible. Device initiated hand-up respectively hand-down can remain a  
28 fall-back solution.

29 Vertical handover [or handoff] is used when a computing environment is based on seamless  
30 connectivity, intelligent network management among heterogeneous network interfaces. Willars  
31 has no concern for any vertical handover.

1  
2       Willars et al disclose that the radio network controller stores cell info for all cells it  
3 controls and all neighboring cells. The RNC's UTRAN will transmit to the mobile  
4 subscriber a list of channels for which the mobile is to measure the signal strength. The  
5 mobile station measures the signal strengths of transmissions received from each of the  
6 neighboring cells and reports the strongest ones, which become candidates for handover.  
7 Willars et al disclose a look-up table @ col. 6, lines 5-12, and in col. 5, lines 25-35 the  
8 controller determines which subset of cells to permit the mobile user to transition into.  
9

10       Willars et al never specifically mention that the position of the E is ever made.  
11

12       However, Carlsson discloses in the Abstract that the position/location of the UE is to be  
13 determined based on timing advanced values. In P.0020 Carlsson discloses that if the  
14 timing advance values are available, the location of the mobile station 80 may be  
15 determined without the need for GPS. Therefore, Carlsson has readily admitted that GPS  
16 may also be used to determine a UE's position. To have provided Carlsson's teaching of  
17 determining a mobile station's location in Willars et al radio network would have been  
18 obvious to a person having ordinary skill in the art because both references are teaching  
19 3rd generation services (3GPP) to a mobile user as the user is moving, or roaming, from  
20 one cell area to another. In P.0003 Carlsson discloses that a mobile terminal will contact  
21 a network via the base station in each cell before being instructed by the communications  
22 system to retune to the next base station. The only reason a mobile station would retune  
23 to another base station is if the signal is getting weak, and the only reason that a signal  
24 would be getting weak is if the UE is moving farther away from the BS's transceiver, i.e.,  
25 roaming, and thus necessitating a handover to another cell site and Base Station.  
26 Therefore, with both Willars et al and Carlsson teaching handovers from one mobile cell  
27 site to another, the skilled practitioner in the wireless arts would have found these  
28 references combinable. Common sense would dictate this substitution.  
29

30       Willars et al also never discloses communicating the cost of services from a  
31 service/control node to a mobile user. However, Englehart does disclose in P.0006 that a  
32 subscriber can access services which are limited by the service plan to which the user  
33 subscribes. In P.0027 & P.0028 Englehart discloses that a service node 114  
34 communicates to the mobile user 122 the capabilities and costs of the service node 114.  
35 To have provided Englehart's disclosure of a node communicating the cost of using the  
36 services of that particular provider in Willars et al communication system would have  
37 been obvious to a person having ordinary skill in these wireless arts because both  
38 references are teaching providing services to a roaming subscriber.  
39       Englehart specifically mentions "roaming" twice in P.0006.  
40

41       Willars et al never specifically disclose a control node's processor measuring the  
42 current load or bandwidth of a particular sector before allowing a handoff. Miernik et al  
43 disclose a roaming mobile phone user. Col. 1, lines 27-42, and soft handoff of that mobile  
44 phone in col. 6, line 29. In col. 12, lines 30-44, Miernik et al disclose that a database 95  
45 contains data regarding service nodes 61. Miernik goes on to disclose that when

1        *processor 92 attempts to select one of the serving nodes, the processor attempts to*  
2        *balance the load between the nodes 61 based on their respective capacities and/or*  
3        *current load. The current load on a serving node may depend on CPU usage, memory*  
4        *usage, occupancy, bandwidth usage, or any other appropriate factor. To have provided*  
5        *Miernik's teaching of the control node's processor measuring the current load/bandwidth*  
6        *of a particular sector before allowing a handover into Willars et al would have been*  
7        *obvious to a person having ordinary skill in the art because if one wireless sector is filled*  
8        *to capacity with users requesting services it would be futile to cram other users into that*  
9        *sector because the QoS would be far less than if the user was placed in a sector where the*  
10       *load was less. Additionally, Miernik et al disclose roaming subscribers in col. 1, lines*  
11       *27-29. Therefore, since all 4 references teach roaming mobile units, a skilled practitioner*  
12       *in these arts would have found these references combinable.*

13      In response, the applicants respectfully states that indeed the office communication in some ways  
14      provides a synopsis of the references, without spelling out what element of claim 1, the portion  
15      of the reference teaches. This is apparently because there is no teaching of all the elements of  
16      claim 1.

17      The combined references fail to show concern or teach or make obvious:

18           any method for managing network resources;  
19           any network control unit;  
20           any execution by a network control unit;  
21           any identifying availability of different communication networks for a communication  
22           device;  
23           any notification of a communication device of a recommendation of identified  
24           communication networks;  
25           any recommendation that is binding;  
26           any informing a communication device to connect to a recommended network;  
27           any rough location of a communication device, or  
28           any identifying of communication networks covering a device's location;  
29           any network lookup table;  
30           any identifying communication networks covering the device's location according to a  
31           look-up table;  
32           any access capability of the communication device to other communication networks;

1 any identifying communication networks covering the device's location and being  
2 accessible for the communication device;  
3 any communication networks recommended according to communication costs;  
4 any communication networks recommended according to a current load;  
5 any communication networks recommended according to bandwidth properties;  
6 any communication networks recommended according to a customer profile;  
7 any hand over process for establishing a communication channel on a recommended  
8 communication network is started after the communication device is notified;  
9 any identification of available networks triggered by a network control unit;  
10 any network availability triggering;  
11 any identification of available networks triggered periodically;  
12 any detection of movement of a mobile communication device;  
13 any identification of available networks triggered when a physical movement of the  
14 communication device is detected; or  
15 the identification of available networks triggered by a capacity shortage on at least one of  
16 the networks;

17 The bits and pieces quoted from the various references fail to make these element obvious. Thus  
18 claim 1 is allowable over the combined references

19  
20 *Applicant's amendment necessitated the new ground(s) of rejection presented in this*  
21 *Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a).*  
22 *Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).*

23 Request is made for the removal of the FINAL status, in as much as the Preliminary Amendment  
24 and the first office action basically crossed each other and applicant was not granted an  
25 opportunity to differentiate from the cited references prior to this reply.

Serial No.: 10/535,574

1 It is anticipated that claim 1 is allowed. Please contact the undersigned for any questions.

2 Please charge any fee necessary to enter this paper to deposit account 50-0510.

3 Respectfully submitted,

4 By: \_\_\_\_\_/Louis Herzberg/\_\_\_\_\_

5 Dr. Louis P. Herzberg

6 Reg. No. 41,500

7 Voice Tel. (845) 352-3194

8 Fax. (845) 352-3194

9 3 Cloverdale Lane

10 Monsey, NY 10952

11 Customer Number: 54856